

MONOTIG 220 IP



Properties

- Operates with 1 Phase 230V-50/60 Hz mains voltage and generators, tolerates voltage fluctuations up to 15%. Extra protection against extremely high or low supply voltages.
- Due to inverter technology, energy efficiency is higher than the conventional machines.
- TIG arc ignition by HF or Lift TIG.
- Excellent welding of thin metals due to very stable low current performance and pulse abilities.
- Advanced TIG settings; Pre-Gas, Slope-Up, Welding Current, Pulse Frequency and Width, Slope-Down, Post-Gas and Crater Filling.
- Due to its coldTIG feature, burr-free, high quality, bright welding seams are obtained.
- Offers 100 JOB memory.
- Interval timer for spot welding.
- 2/4 Triggering and Current Adjustment via torch and foot pedal.
- Welding parameters are monitored on the digital display.
- Excellent welding characteristics for rutile and basic electrodes.
- Advanced Stick Electrode options; Hot Start for easy ignition, Arc Force for arc stability, Anti Stick to prevent electrode sticking.
- VRD for hazardous environments such as mines.
- Stable welding current without loss of performance due to electric line fluctuations or with long welding and electrical cables.
- Portable design, withstands tough working conditions.
- Fan cooling and thermal protection against overheating.
- Standard accessories come with the machine.

Technical Specifications

Power Source




Mains Voltage (1Ph)

230





V

Input Power (MMA)	9,2 (%15)	kVA
Input Power (TIG)	8,05 (%20)	kVA
Welding Current Range	3 - 220	ADC
Nominal Welding Current	220 (%20)	ADC
Open Circuit Voltage	87	VDC
Electrode Diameter	2.00 - 5.00	mm
Tungsten Electrode Diameter	1.00 - 2.40	mm
Dimensions (l x w x h)	474 x 221 x 395	mm
Weight (Net)	15.5	kg
Cooling Type	Hava	
Protection Class	IP21	

Standard Accessories

Accessories Picture	Code	Name	
	7907000002	Gas Hose	Standard
	7110018004	LAVA TIG 26-4	Standard
	7905201603	Ground Clamp And Cable	Standard

Opsiyonel Aksesuarlar

Accessories Picture	Code	Name	
	7910000120	TIG AYAK PEDALI	Optional
	7906201603	Electrode Clamp And Cable	Optional
	7910000140	TIG AYAK PEDALI	Optional
	7020001004	Argon Regulator	Optional