

# BMK-2Y-300

## ELECTRODE DRYING OVEN WITH MANUEL THERMOSTAT

<b>CAPACITY</b>	2 PACK – 200 STICKS* - 10 KG
<b>HEIGHT</b>	60 CM
<b>DIAMETER (OUT)</b>	21 CM
<b>TEMPERATURE</b>	50-300 °C
<b>ELECTRIC POWER</b>	400 W
<b>ELECTRIC VOLTAGE</b>	220-240 V
<b>TOTAL CURRENT</b>	2 A
<b>WEIGHT</b>	8 KG
<b>PACKAGE SIZES</b>	34x27x68 CM

\*It varies according to the electrode diameter.

The main operating principle is to move the electrode to the application points after oven drying of the factory output electrodes in the main oven and keep them at a certain temperature at the application point.

The main function is to transport the electrodes which are free from moisture after the process of shocking under 350 °C and resting them under 130 °C, and also to keep the application points where there will be electrical connection manually in 50-200 °C temperature range in order to keep them at the desired temperature. It can be used with all kinds of electrodes easily.



**OUR COMPANY HAVE ISO 9001:2008  
ISO 18001 OHSAS, CE CERTIFICATES.  
IF DESIRE TO BE CERTIFIED TÜRK-AK TS-EN ISO-IEC 17025 CAN DEVICES ARE MADE CALIBRATION**

