

BMTSD-250

SUBMERGED WELDING POWDER DRYER WITH DOUBLE DIGITAL THERMOSTAT

CAPACITY	250 KG + 250 KG
HEIGHT	50 -140 CM
LENGTH- WIDTH	275 x 75 cm
TEMPERATURE	0-400 °C
ELECTRIC POWER	4500 W + 4500 W
ELECTRIC VOLTAGE	380 V
TOTAL CURRENT	42 A
WEIGHT	390 kg

Before finalizing the shocking process is complete in standard ovens, new flux powder shall not be placed, the resting process shall be applied to the shocked flux and when the flux are finished all, new product can be taken into process, in this sense, the main operating principle is to carry out both of these 2 processes, in one section carrying out the shocking process while carrying out the resting process on the other section.

After the flux powder at factory output are put to shocking process in shocking ovens at 300 °C they are to be taken to 130 °C temperature level and they shall be taken to resting process than they shall be taken into welding process. This process is not frequently carried out in busy workshops with standart ovens. In this product, there are two seperate sections with two independent digital thermostat this allowing shocking process in one section while carrying out the resting process in the other which provides a special application for busy workshops.

**DOUBLE
CONTROL PANELS**





OUR COMPANY HAVE ISO 9001:2008
ISO 18001 OHSAS, CE CERTIFICATES.
IF DESIRE TO BE CERTIFIED TÜRK-AK TS-EN ISO-IEC 17025 CAN DEVICES ARE MADE CALIBRATION

